

In The Specification:

Please amend the title as follows:

A1 CONTROL METHOD AND ELECTRONIC DEVICE ENABLING RECOGNITION OF
FUNCTIONS INSTALLED IN THE ELECTRONIC DEVICE

Please replace paragraph [0004] with the following rewritten paragraph:

A2 [0004] If the main unit does not recognize a function to be performed by the electronic device, inappropriate data may be transmitted and, hence, erroneous processing may be performed. At the main unit side, a malfunction may result. When the main unit requests a function not installed in the electronic device, that function cannot be executed and, as a result, the main unit may go down. Also, it may require time and a complicated procedure to restore the main unit to ~~it's~~its original state.

Please replace paragraph [0005] with the following rewritten paragraph:

A3 [0005] The problems with the conventional electronic device include erroneous processing and main unit malfunctions caused by the inability of the main unit to recognize a function to be executed by the electronic device. When a function is not executed, the main unit may go down, and it may require time and a complicated procedure to restore the main unit to ~~it's~~its original state.

Please replace paragraph [0009] with the following rewritten paragraph:

A4 [0009] According to the present invention, it is possible to enable a main unit to recognize a function to be executed by an electronic device, and hence a desired function is reliably executed by using a simple method. The main unit can reliably enable a desired function. Also, the main unit can easily recognize a function installed in the electronic device. It is therefore possible to prevent unnecessary operations and malfunctions such as the activation of an unexecutable function. Even when a list of functions is not provided, it is still possible to prevent unnecessary operations and malfunctions such as the activation of an unexecutable function. As a result, the present invention can solve problems encountered with a conventional electronic device. Such problems include erroneous processing and main unit malfunctions due to the main unit's inability to recognize a function to be executed by the electronic device, which may require time and a complicated procedure to restore the main unit to ~~it's~~its original state.

Please replace paragraph [0036] with the following rewritten paragraph:

A5 [0036] In a conventional electronic device, erroneous processing and main unit malfunctions result from the inability of the main unit to recognize the function executed by the electronic device. When a function is not executed, the main unit may go down, and it may require a complicated procedure and time to restore the main unit to ~~it's~~its original state.

Application No.: 09/834,025

Docket No.: SONYJP 3.0-154

According to the present invention, the above problems are easily solved.